



The slender deck is supported on trunk-like piers of Corten steel

# LIVING LABORATORY

A new footbridge intended to be a testing ground for structural health monitoring systems is being built at Princeton University in the USA. Branko Glisic explains

Many of the students set to use Princeton University's new footbridge when it opens in autumn this year will be unaware that they are also participating in a research and educational programme. Conversely some of the students from the university's civil engineering department will be all too knowledgeable about the structure, having helped to instrument and monitor it.

Created as a part of Princeton University's Natural Sciences neighbourhood, the bridge will connect the western campus, which houses the Lewis-Sigler Institute for Integrative Genomics in the Icahn Laboratory and will have a new neuroscience and psychology building, currently under design, with the eastern side which is home to Jadwin Hall physics building, a new chemistry building, and Lewis Library.

As well as its functional purpose the bridge also has strong symbolic and aesthetic impacts; in addition, it is equipped with various monitoring systems with the intention of transforming this structure into a multipurpose research and teaching laboratory in the field of structural health monitoring and beyond.

According to designer Christian Menn, the alignment was more or less set; the bridge had to cross the main road and an access road to the Princeton Football Stadium, as well as connecting three university buildings. A smoothly-curved x-alignment on plan satisfied all these requirements. The bridge is situated in a wooded area; Menn's approach is always to try and preserve the existing landscape and to integrate his bridges as much as possible. For this reason he avoided use of a cable-stayed structure and proposed a light, elegant deck supported by branched columns formed of dark brown Corten steel. The single, slender columns result in an extremely transparent bridge, with the columns difficult to distinguish from the trunks of the trees.

The structural system is unusual; the deck balances on a single, hinged arch, which runs along the central axis of the deck, and which is laterally stiffened by the deck. The analysis and the structural detailing of the bridge was quite demanding, says Menn, which is one of the reasons the structural engineering department used an extensive system of instruments to check the actual behaviour of the bridge.

The Streicker Bridge has a main span and four approach 'legs' creating the x-shape. Structurally, the main span is a deck-stiffened arch and the legs are curved continuous girders supported by steel columns. The legs are horizontally curved and the shape of the main span follows this curvature. Arch and columns are weathering steel while the deck is reinforced post-tensioned concrete. The slender and elegant deck-stiffened arch represents an efficient solution to bridge the span of 35m keeping the deck thickness of only 578mm and arch diameter of 324mm. Detailed design was carried out by HNTB.

The information obtained from structural health monitoring is used to plan and design maintenance activities, increase safety, verify hypotheses, reduce uncertainty, and widen the knowledge concerning the structure being monitored. The need for such monitoring has rapidly increased, but despite this it is rarely used on real structures since an efficient approach for implementation has yet to be developed.

Structural health monitoring has been applied to the Streicker Bridge with the aim of transforming it into an on-site laboratory for various research and educational purposes related but not limited to structural health monitoring.

Research will focus on an efficient general approach for widespread implementation of SHM, and it will address important SHM challenges such as collecting the long-term data sets necessary for understanding the real structural behaviour; identifying change in strain patterns caused by unusual behaviour and establishing robust damage detection algorithms. Four fields of research will be studied; monitoring methods for deck-stiffened arches and curved continuous girders; long-term performance of short-gauge, long-gauge and truly distributed sensors; development and testing of new sensors and monitoring systems, and SHM related to Streicker Bridge itself to verify the design, study long-term performance of the bridge, and long-term monitoring benefits.

Structural health monitoring of this bridge will also serve as a support to the university course on SHM and several other courses related to structural analysis and design, as well as to short courses given to practitioners.

Two fibre-optic sensing technologies are currently deployed: discrete long-gauge sensing technology based on Fibre Bragg-Gratings and truly distributed sensing